

DD 12180 - 12V 18Ah - C20





Features


- Special grid alloy and plate design
- Long service life
- High charging performance
- High gas recombination technology
- Low-self discharge characteristic
- Wide operating temperature range

Application

- Measuring instrument
- Medical equipments
- Telephone sets
- Lighting equipment
- Security & alarm systems
- UPS power supply
- Power station and telecom station



F6 Terminal




Specification

Cell per unit	6
Norminal Voltage	12V
Norminal Capacity	18 Ah
Weight	Approx. 5,27 Kg (11,620 lbs)
Internal Resistance	Approx. 12,42 mΩ
Norminal Operating Temperature Range	25°C
Recommended Maximum Charging Current Limit	4,5 A
Float Charging Voltage	13,6 to 13,8VDC/unit Average at 25°C (77°F)
Equalization and Cycle Service	14,1 to 14,4VDC/unit Average at 25°C (77°F)
Self Discharge	Reddot Batteries can be stored for more than 6 months at (25°C/77°F).Please charge batteries before using. For higher temperatures the time interval will be shorter.
Terminal	F6

Characteristics


Rated Capacity	20 hour rate(0,9A)	18,4AH
	10 hour rate(1,8A)	16,8AH
	5 hour rate(2,88A)	14,4AH
	27 min rate(18A)	8,1AH
	7 min rate(54A)	6,3AH

Charging Characteristics(25°C/77°F)




The Relation between Discharging


Current and Discharging time(25°C/77°F)



Discharging Characteristic(25°C/77°F)



Self-Discharging Characteristic(25°C/77°F)



Constant Current Discharge Characteristics (Amperes at 25°C)

Cut-off Voltage/cell	5min	10min	20min	45min	1Hr	2Hr	4Hr	8Hr	10Hr	20Hr
1,70	66,6	43,3	24,25	12,60	10,80	6,40	3,64	2,060	1,720	0,920
1,75	66,0	42,9	24,03	12,44	10,75	6,15	3,56	2,040	1,700	0,910
1,80	65,3	42,5	23,72	12,28	10,69	5,91	3,47	2,020	1,680	0,900

Constant Power Discharge Characteristics (Watts at 25°C)

Cut-off Voltage/cell	5min	10min	20min	45min	1Hr	2Hr	4Hr	8Hr	10Hr	20Hr
1,70	799	520	291	151	130	76,76	43,73	24,78	20,43	11,01
1,75	792	515	288	149	129	73,90	42,78	24,56	20,22	10,91
1,80	754	509	285	147	128	70,94	41,72	24,25	20,01	10,69

All mentioned values are average values