

VRLA Rechargeable Battery

HR50-12 (HR50-12FR)



FEATURES

- Maintenance free(no water topping-up required).
- No free acid(Non-spillable battery).
- Low self-discharge rate, lower than 3% capacity loss per month.
- Can be used in any orientation(excluding used inverted).
- The battery is designed for high rate usage.
- Absorbent Glass Mat technology for efficient gas recombination.
- The power density at 5 min~15min discharging rate is 30% higher than BP series.

APPLICATION

- UPS
- Wheelchairs
- Golf-Carts



SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	48Ah @ 10 hour rate F.V.(1.75V/cell)
Approx. Weight	15.3Kg(33.74lbs.)
Terminals	B2 (Fitting M5 bolt & nut) , I1 and I2 are optional
Internal Resistance	≤5mΩ (Fully Charged)
Max. Discharge Current	600 A (5 sec.)
Max. Charge Current	14.4 A
Operating Temperature Range	Charge : 0°C~40°C(32°F~104°F) Discharge : -20°C~50°C(-4°F~122°F) Storage. : -20°C~40°C(-4°F~104°F)
Container Material	ABS(UL94-HB, UL94-V0 is optional)

ISO 9001	ngs ISO 9001 REGISTERED	UKAS REGISTERED
ISO14001	WSC ISO14001	
UL	UL MH19884	
CE	CE C4M20310-2474-E-16	
<ul style="list-style-type: none"> • IEC 61056-1 • JIS C 8702-1 • GB/T 19639.1 		

DIMENSION(mm/inch)

OUTER DIMENSIONS

TERMINAL TYPE

Length

197±1.5 (7.76±0.06)

Width





165±1.5 (6.50±0.06)

Container Height

171±1.5 (6.73±0.06)

Total Height


171±1.5 (6.73±0.06)



Terminal Hardware Initial Torque: B2/I1(4.0Nm±5%),I2(5.5Nm±5%)


Terminal I1

M5x0.8



Terminal I2

M6x1.0



Constant power discharge characteristics at 25 °C/77 °F

Unit: W

F.V. (V/cell)	Discharge Time	5 Min	10 Min	15 Min	20 Min	30 Min	40 Min	50 Min	60 Min	120 Min
1.80V		2050.0	1400.0	1014.0	865.0	658.0	500.0	418.0	368.0	202.8
1.70V		2450.0	1563.0	1103.0	916.0	685.0	519.0	431.0	376.0	206.7
1.60V		2625.0	1644.0	1153.0	950.0	700.0	531.0	440.0	383.0	210.0
1.50V		2700.0	1675.0	1178.0	965.0	709.0	538.0	445.0	386.0	211.1
1.40V		2750.0	1698.0	1191.0	974.0	714.0	541.0	449.0	389.0	211.7
1.30V		2775.0	1713.0	1200.0	980.0	718.0	544.0	451.0	390.0	212.2

Constant current discharge characteristics at 25 °C/77 °F

Unit: A

F.V. (V/cell)	Discharge Time	5 Min	10 Min	15 Min	20 Min	30 Min	40 Min	50 Min	60 Min	120 Min
1.80V		183.04	122.81	87.72	74.19	55.76	42.05	34.98	30.67	16.90
1.70V		222.73	137.11	95.42	78.56	58.05	43.65	36.07	31.33	17.23
1.60V		238.64	144.21	99.74	81.48	59.32	44.66	36.82	31.92	17.50
1.50V		245.45	146.93	101.90	82.76	60.08	45.25	37.24	32.17	17.59
1.40V		250.00	148.95	103.03	83.53	60.51	45.50	37.57	32.42	17.64
1.30V		252.27	150.26	103.81	84.05	60.85	45.75	37.74	32.50	17.68

All data shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.